

**AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of the Claims**

1. (currently amended) A bearing comprising:  
a temperature conducting housing;  
a bearing element disposed within the housing;  
an oil sump to house lubricant for the bearing element;  
~~at least one~~ a plurality of motor driven electric fans mounted to the bearing housing, wherein the ~~at least one fan is~~ plurality of motor driven electric fans are adapted to transfer heat from the bearing housing by forced convection; and  
a temperature sensor disposed within the bearing housing adjacent to the bearing element and adapted for determining a temperature within the bearing housing; and  
a logic controller coupled to the temperature sensor and operable to selectively operate each of the plurality of motor driven electric fans based on the temperature within the bearing housing.
2. (currently amended) The bearing of claim 1, wherein the bearing housing includes an oil sump, and wherein the at least one of the plurality of motor driven electric fans fan is disposed adjacent to the oil sump.
3. (original) The bearing of claim 1, wherein the bearing housing includes a plurality of cooling fins.
4. (canceled).

5. (previously presented) The bearing of claim 1, wherein the temperature sensor is adapted for determining the temperature of the bearing element.

6. (previously presented) The bearing of claim 1, wherein the temperature sensor is adapted for determining the temperature of an oil sump within the bearing housing.

7. (currently amended) The bearing of claim 1, ~~further comprising a logic controller electrically coupled to the at least one fan and to the temperature sensor wherein~~ the logic controller is adapted to receive a signal from the temperature sensor, process the signal, and selectively operate each of the plurality of motor driven electric fans ~~the at least one fan~~ according to the received signal.

8. (original) The bearing of claim 7, wherein the signal from the temperature sensor is generated according to the temperature within the housing.

9. (currently amended) The bearing of claim 8, wherein an upper temperature limit is pre-selected and wherein the logic controller is adapted to turn ~~the~~ at least one motor driven electric fan on based upon a relationship between a sensed temperature and the upper temperature limit.

10. (currently amended) The bearing of claim 9, wherein a lower temperature limit is pre-selected and wherein the logic controller is adapted to turn the at least one motor driven electric fan off based upon a relationship between a sensed temperature and the lower temperature limit.

11. (currently amended) The bearing of claim 18, wherein ~~the at least one fan~~  
plurality of motor driven electric fans comprises at least one primary fan and at least one  
secondary fan.

12. (original) The bearing of claim 11, wherein a first temperature limit is  
pre-selected and wherein the logic controller is adapted to turn the at least one primary  
fan on based upon a relationship between a sensed temperature and the first temperature  
limit.

13. (original) The bearing of claim 12, wherein a second temperature  
limit is pre-selected and wherein the logic controller is adapted to turn the at least one  
secondary fan on based upon a relationship between a sensed temperature and the second  
temperature limit.

14. (original) The bearing of claim 13, wherein a third temperature limit is  
pre-selected and wherein the logic controller is adapted to turn the at least one secondary  
fan off based upon a relationship between a sensed temperature and the third temperature  
limit.

15. (original) The bearing of claim 14, wherein a fourth temperature limit  
is pre-selected and wherein the logic controller is adapted to turn the at least one primary  
fan off based upon a relationship between a sensed temperature and the fourth  
temperature limit.

16. (currently amended) The bearing of claim 18, wherein ~~the at least one fan~~  
is each of the plurality of motor driven electric fans are adapted to operate at variable speeds  
and wherein the logic controller is adapted to control the speed of each of the plurality of  
motor driven electric fans ~~the at least one fan~~.

17. (currently amended) A method for controlling the temperature of a bearing having a housing and a bearing element disposed within the housing, the method comprising:

mounting ~~at least one fan~~ a plurality of fans on the bearing housing to remove heat from bearing element lubricant disposed within the bearing housing;

disposing a temperature sensor within the bearing housing adjacent to the bearing element;

electrically coupling a logic controller between the ~~at least one fan~~ plurality of fans and the temperature sensor; and

adapting the logic controller to receive a signal from the temperature sensor and to operate the fan at least one of the plurality of fans at various speeds in response to the signal received.

18. (canceled).

19. (previously presented) The method of claim 17, wherein the housing includes an oil sump and disposing a temperature sensor comprises disposing the temperature sensor adjacent to the bearing element and within the oil sump.

20. (currently amended) The method of claim 17, comprising pre-selecting a temperature range in which the fan plurality of fans will operate.

21. (currently amended) The method of claim 17, wherein mounting the ~~at least one fan~~ plurality of fans comprises mounting at least one primary fan and at least one secondary fan.

22. (original) The method of claim 2117, comprising pre-selecting at least first and second temperature limits and adapting the logic controller to operate at least one primary fan in response to a signal received which corresponds to the first temperature limit and to operate at least one secondary fan in response to a signal received which corresponds to the second temperature limit.

23. (currently amended) A bearing comprising:  
a housing;  
means for mounting a at least one bearing element disposed within the a housing;  
means for mounting a plurality of fans within the housing~~introducing forced air flow over an exterior surface of the bearing housing;~~  
~~means disposed adjacent to the bearing element for discerning a temperature of the bearing element; and~~  
means for variably controlling the amount of forced air flow plurality of fans in correlation with the temperature discerned of the bearing element.

24. (currently amended) The bearing of claim 23, ~~wherein the housing includes an oil sump, and wherein the means for introducing forced air flow includes a fan disposed adjacent to the oil sump~~ means for storing oil.

25. (canceled).

26. (currently amended) A system comprising:  
a plurality of bearings, each bearing including a thermally conductive housing, and a bearing element disposed within the housing;  
a plurality of fans affixed to the housing of each bearing;  
a temperature sensor disposed within the housing of each bearing adjacent to the bearing element and corresponding to the fans affixed on the same bearing; and

a logic controller adapted to receive a signal from each temperature sensor and to operate at least one of the corresponding fans at various speeds according to the received signal.

27. (previously presented) The system of claim 26, further comprising an oil sump formed in each bearing housing, and wherein at least one of the fans is disposed adjacent to each oil sump.